

P/N	PS-SPD-0650MNFABU
Watts	650W
Watts	650W
Bronze polumodularno	
RGB FAN	No
MODEL	SP-650AH3CCB-B SF
TYPE	ATX 12V v2.4 and EP
MAX. OUTPUT CAPACITY	650W
Color	Black
DIMENSION (W / H / D)	150mm(W) x 86mm(l
PFC (POWER FACTOR CORRECTION)	Active PFC
POWER GOOD SIGNAL	100-500 msec
HOLD UP TIME	> 12msec at 80% of full load at 230Vac input
INPUT CURRENT	10A max. 6 - 12A
INPUT FREQUENCY RANGE	47Hz -63Hz
INPUT VOLTAGE	100V-240V~
OPERATING TEMPERATURE	0°C to +40°C +5°C to +40°C
OPERATING HUMIDITY	20% to 90%,non-condensing 20% to 85%,non-condensing
STORAGE TEMPERATURE	-20 °C to +70 °C -40 °C to +55 °C
STORAGE HUMIDITY	5% to 95%, non-condensing 10% to 95%, non-condensing
COOLING SYSTEM	140mm Fan: 2300 R.P.M. ± 10%
EFFICIENCY	Meet 80 PLUS®Bronze at 115Vac input.
MTBF	100,000 hrs minimum
SAFETY APPROVAL	cTUVus/TUV/CE/FCC/S-mark/EAC/BSMI/C-TICK/CCC
PCI-E 6+2PIN	4
PROTECTION	OVP ,OPP, OCP, OTP

