

Wireless Router Tenda TX2L Pro

Wi-Fi

AX15002.4:300Mbps5Ghz:1201Mbps3xGLAN1xGBWAN

MU-MIMO

Šifra: 36990

Kategorija proizvoda: RUTERI

Proizvođač: Tenda

Cena: 3.419,00 rsd.



IEEE 802.11ax Beamform

standardi

Ostali standardi

IEEE 802.3, IEEE 802.3u, IEEE 802.3ab

Ujedinjenje Wi-Fi mreža

Da, moguće je ujediniti 2,4 GHz i 5 GHz u jednu Wi-Fi mrežu

Frekvencija i EIRP

2.4G: 2412-2472MHz (CH1-CH13), 5G: 5180-5240MHz (CH36-CH64), <20 dBm (2.4 GHz), <23 dBm (5 GHz)

Sigurnost Wi-Fi

WPA3-SAE, WPA-PSK, WPA2-PSK, WPA/WPA2-PSK, WPS (Wi-Fi Protected Setup)

Bežični režimi

Wireless Router, AP mode, Universal Repeater (Client+AP, WISP)

Brzina prenosa

5GHz: do 1201Mb/s, 2.4GHz: do 300Mb/s

Interfejs

1x Gigabit WAN (10/100/1000 Mb/s), 3x Gigabit LAN (10/100/1000), 1x dugme WPS/Reset

DHCP

DHCP Server, DHCP Client List, DHCP Static IP Address Reservation and Assignment

Povezivanje na Internet	Dynamic IP, Static IP, PPPoE, Unifi, Maxis, Maxis-special, Celcom, Digi, Manual
Virtuelni server	Port Forwarding, DMZ Host, UPnP
Sigurnost	Filtrovane i klijenata, roditeljska kontrola
DDNS	No-ip, 88ip, Oray.com, DynDNS
VPN	IPSec Transparent Transmission, PPTP Transparent Transmission, L2TP Transparent Transmission, PPTP VPN Server, PPTP VPN Client, L2TP VPN Client
Način upravljanja	HTTP, Daljinsko web upravljanje, SMART aplikacija za mobilni telefon
Specijalne funkcije	Wi-Fi+ Mesh, Smart Traffic Prioritisation, Smart Wi-Fi Schedule, Smart LED On/Off, Tenda Cloud
Firewall	ICMP Flood Attack Defense, TCP Flood Attack Defense, UDP Flood Attack Defense, Ignore Ping Packet From WAN Port
Firewall i ostalo	IPv6, IPTV, Mreža za goste, VLAN, Kontrola propusnog opsega, MAC Clone, Static Routing, System Log, Network Time, Backup/Restore Settings, online ažuriranja firmvera
LED indikacija	1x Sys
Antena	5x 6 dBi
Provedba	indoor, desktop
Napajanje	12 V DC, 1A
Hlađenje	Pasivno
Radna temperatura	0° do 40 °C

Dimenzije (v
x š x d)

244